



Versatile enough to accommodate upscale residential and commercial applications. Allows up to 1 3/8" triple pane insulated glass and utilizes Roto X-Drive operators. It meets or exceeds current energy performance requirements.



Casement Window

Classic detailing with Compression Seal Technology limits air, water and noise infiltration.

Toll Free: 800.318.9442

minnkotawindows.com

Casement Window



	Dual Pane LoE 180	Dual Pane LoE 272	Dual Pane LoE 366	Triple Pane LoE 272	Triple Pane Double LoE 272
U-Factor	0.26	0.26	0.25	0.21	0.17
SHGC	0.40	0.26	0.17	0.24	0.22
VT	0.48	0.44	0.39	0.40	0.35
Condensation Resistance	62	63	63	72	81
AI	.04 cfm/ft ²				
Water Resistance	15.04 psf				
Design Pressure	+/- 60.15 psf				

Frame	Rehau uPVC
Frame Size	3-1/4
Exterior Colors	Almond, Brick Red, Bronze, Brown, Clay, Dakota Sand, Forest Green, Gray, Mocha, White, Custom
Interior Colors	Almond, Clay, Dark Woodgrain, Heartwood, Irish Oak, Maple, White
Grille Colors	All interior and exterior colors available and brass
Grille Type	Flat, Contour, Slimline, Simulated Divided Light
Grille Pattern	Colonial, Prairie, Farmhouse, Suspended
Brickmould	1 1/2" Std. w/fin, 1 1/2" Std. cut for J-Channel, 1 1/2" Retro, 1 1/2" Retro w/Sill, 2" Std. w/fin, 2" Std. w/Sill, 2" Retro, 2" Retro w/Sill, 3 1/2" w/fin, 3 1/2" w/Sill
Glass Strength	Annealed, Tempered
Glazing	Interior
Glazing Type	blink BLINDS + GLASS w/ LoE 272, Dual LoE 180/Argon, Dual LoE 272/Argon, Dual LoE 366/Argon, Insulated Clear, Triple LoE 180/Argon, Triple LoE 272/Argon, Triple LoE 366/Argon, Triple Double LoE 272/Argon, Triple Double LoE 180/Argon
IG Thickness	13/16" oa. Dual, 1 3/8" oa. Triple Pane
Spacer	Endur
Interior Returns	Jamb, Drywall
Extension Jamb Loose	Almond, Clay, Dark Woodgrain, Heartwood, Irish Oak, Maple, White
Extension Jamb Applied	Almond, Clay, Dark Woodgrain, Heartwood, Irish Oak, Maple, White
Maximum Frame Width	38"
Minimum Frame Width	15"
Maximum Frame Height	72"
Minimum Frame Height	23"